



P Type Swing Barrier

For Office , Hospitals & Commercial purpose
SP SWB Single / Double Flap



SP SWB P 01

SP SWB P 02

Applications

- Wider passage for Wheel Chair / Goods at Offices / Hospitals / Airports / Malls

Features

- Stainless Steel # 304 body
- Bi Directional / Uni Directional
- For 600~1200 mm Wider Passage
- Stainless Steel Stronger Flap
- Passenger counter (Optional)
- Direction and Lane LED Indicator
- Passenger count 20 / Min
- Protection grade IP 55
- 230V / 50 Hz / 30 W power
- It can be integrated with third party RFID/ Biometric / Face / QR code readers

Model	SP SWB P 01	SP SWB P 02
AC Input Voltage	230V / 50Hz / 1 P	230V / 50Hz / 1 P
AC Input Power	30 W	30W X 2
Dimension	980 H x 420 W x 330 D mm	980 H x 420 W x 330 D mm X 2
Flap Type	Single (One Side)	Single (Two Side)
Passage Width	800 mm	1600 MM
Pass Speed	< 20 Person / Min	< 20 Person / Min
Box Type	Stainless Steel # 304	Stainless Steel # 304
Motor Type	DC 12V	DC 12V
Operating Condition	-15 ~ 60 Deg C	15 ~ 60 Deg C
Humidity	< 95%	< 95%

* Specification are subjected to change for improvements