



## Flap Gates

**For Commercial & Industrial purpose**

**SP FLP Single / Double**

### Applications

- For People restricted Entry / Exit at Office / Parks / Industry / Schools

### Features

- Stainless Steel # 304 body
- Bi Directional / Uni Directional
- Acrylic Transparent 12 mm Flap
- LED Light on Flap
- Passenger counter (Optional)
- Direction and Lane LED Indicator
- Passenger count 35 / Min
- Protection grade IP 55
- 230V / 50 Hz / 30 W power
- Suitable for Outdoor use (with Canopy)
- It can be integrated with third party RFID/ Biometric / Face / QR code readers



SP FLP Single

SP FLP Double

SP FLP Single

Model	SP FLP SINGLE	SP FLP DOUBLE
AC Input Voltage	230V / 50Hz / 1 P	230V/50Hz/1P
AC Input Power	30 W	30 W
Dimension	980 H x 300 W x 1000 D	980 H x 300 W x 1000 D
Flap Type	Single (One Side)	Double( Both side)
Passage Width	550 mm	550 mm
Pass Speed	≤ 35 Person / Min	≤ 35 Person / Min
Box Type	Stainless Steel # 304	Stainless Steel # 304
Motor Type	DC 12V	DC 12V
Operating Condition	-15 ~ 60 ° C	-15~60 ° C
Humidity	≤ 95%	≤ 95%

\* Specification are subjected to change for improvements