



**Auto Revolving Door**

**For Malls, Hotels & Offices**  
SP GSD REV



Vertical type  
Model - SP TST VER

**Applications**

- Auto Revolving Doors are used where Human Traffic is high & Air cooling isolation is needed. It also maintains air pressure intact.

**Features**

- European Controller & Sensors
- German Motor 100% Duty cycle
- 3 Wing / 4 Wing (Optional)
- Stainless Steel Structure with Canopy
- Toughen Glass on Aluminum frames
- 230V / 50 Hz / 500 W power
- Aluminum powder coated ceiling with Light
- Protection sensor for Human Traffic
- Customized design as per need

| Model            | SP GSD REV                             |
|------------------|----------------------------------------|
| AC Input Power   | 230V / 50Hz / 500 W                    |
| Door Height      | 2450 H mm (2150 + 300 Canopy)          |
| Door Diameter    | 3160 mm                                |
| Canopy Cladding  | SS#304 or Aluminum                     |
| Ceiling          | Aluminum Powder Coated with LED lights |
| Motor            | German Lenze 180 W or similar          |
| Reducer & Braker | German Lenze                           |
| Controller       | Panasonic Japan                        |
| Touch Panel      | Panasonic Japan                        |
| Radar & Sensor   | BEA Belgium                            |

**Customised Size Available  
(3 Wing / 4 Wing Options)**

\* Specification are subjected to change for improvements