



Full Height Turnstile

For Commercial & Industrial purpose
SP TST FH



SP TST FH 01



SP TST FH 02

Applications

- For People restricted Entry / Exit at Office / Parks / Industry / Schools

Features

- Stainless Steel # 304 body
- Bi Directional / Uni Directional
- Compatible with All Access Control
- Passenger counter (Optional)
- Direction and Lane LED Indicator
- Passenger count 25 / Min
- Protection grade IP 55
- 230V / 50 Hz / 1 W power
- Suitable for Outdoor use (with Canopy)
- It can be integrated with third party RFID/ Biometric / Face / QR code readers

| Model | SP TST FH01 | SP TST FH02 |
|---------------------------|-----------------------------|--------------------------|
| AC Input Voltage | 230V / 50Hz / 1 P | 230V/50Hz/1PAC |
| Input Power | 50 W | 50 W |
| Dimension | 2300 H x 1500 W x 1600 D mm | 2300 H x 1450 W x 2300 D |
| Passage Width | 620 mm | 630 mm |
| Pass Speed | < 25 Person / Min | < 25 Person / Min |
| Box Type | Stainless Steel # 304 | Stainless Steel # 304 |
| Wings / Angle of Rotation | 3 Wings / 120 ° | 4 Wings / 90 ° |
| Operating Condition | -15 ~ 60 Deg C | -15~60 Dec C |
| Humidity | < 95% | < 95% |
| Life Cycle (MTBF) | 6 Million | 6 Million |

* Specification are subjected to change for improvements